



Back-UPS Connect

Reliable and affordable power protection for networking devices

Introducing APC Back-UPS™ Connect - an uninterruptible power supply (UPS) designed specifically to power compatible routers/modems, VoIP systems and other smart home devices during a power outage.

The new Back-UPS Connect is a reliable, flexible and affordable 12V DC UPS with lithium-ion battery ensuring service continuity for connected equipment during power outages.

That's Certainty in a Connected World.



CP12036LI

apc.com

Life Is On



Designed to keep your network devices such as routers, smart home assistants connected and online during power outages.



Why choose APC Back-UPS Connect?



Reliable connectivity

Keeps your connected devices online and operating during power outages



Flexible compatibility

Comes with 2 additional pair for a total of 3 different DC output connector tips to ensure compatibility with multiple networking devices



Long runtime

Up to 4 hours of runtime

Ideal Applications



Router



Smart Home Assistant



VoIP Phone System



IP Camera

Standard Features

DC Input/Output

Designed to support various 12 Vdc (2.5mm default DC tip) networking applications such as modems and routers.

Multiple DC Tips

Comes with 2 additional pair of DC tips (2.1mm and 1.7mm) to ensure compatibility with different brands of networking gear with 12V rating.

Lithium-ion Battery

Provides significantly longer service life than traditional VRLA battery.

Long Runtime

Up to 4 hours of runtime for an average router to ensure reliable connectivity.

Compact Design

Small footprint for easy installation in tight spaces.

LED Indicators

Easy to read indicators providing battery capacity information.

Back-UPS Connect

SKU technical specifications



CP12036LI						
Power rating (Watt)	36 W					
Input						
Nominal input voltage	12 Vdc					
Input voltage range	11.4 - 12.6 Vdc					
Input current	4.1 A (max)					
Input over current protection	15 A fuse (fast acting fuse)					
Output						
Nominal output voltage	12 Vdc					
Output current	0 - 3 A					
Transfer time	0 ms @ 3 A load					
Input/Output configuration						
Input connector	Barrel - center pin 2.5 mm; 5525 DC jack (default)					
Output cable length	80 cm					
Output connector	Barrel - center pin 2.5 mm; 5525 DC jack (default)					
Additional DC tips	2.1 mm and 1.7 mm					
Battery and Runtime						
Battery type	Lithium-ion					
Battery pack capacity	27.75 Wh					
Runtime estimates	5 W	6 W	9W	20 W	29 W	36W
	240 mins	200 mins	120 mins	60 mins	45 mins	30 mins
Typical recharge time	12 hours					
User interface						
Display	LED indicators (power and battery level)					
Power button LED	Bi-color red and green LED					
Capacity indicator	4 green LEDs (each LED represents 25%)					
Physical						
Dimensions W x H x D (mm)	99 x 25 x 109					
Net weight	0.3 kg (0.67 lbs)					
Environment						
Operating temperature	0°C to 40°C					
Operating humidity	0 to 90% non-condensing					
Operating elevation	0 to 5,000 m at 100% load					
Audible noise	<40 dB					
Protection class	IP20					
Conformance						
Certifications	CE (IEC/EN 62368-1, EN 55032 class B, EN 55035), UKCA, KC, RCM, UN38.3, RoHS3					
Standard warranty	2 years					

Life Is On



One Boston Place
Floor 27
Boston, MA 02108
United States
www.apc.com

© 2023 Schneider Electric. All Rights Reserved. Schneider Electric | Life Is On, APC, and Back-UPS are trademarks and the property of Schneider Electric SE, its subsidiaries, and affiliated companies. All other trademarks are the property of the respective owners.